

YOUR
SMART
ENERGY

# **BATTERY**

# **SMILE-G3-BAT-4.5S**

# **RESIDENTIAL SERIES**

# **CAPACITY**

4.5 kWh Modular





# **KEY FEATURES**

**Redundancy Design** 

**High Efficiency and Safe** 

**Simple Installation and Maintenance** 

**Bypass Function** 

# careful editing - liability the time of printing. Subject to modifications. All information is without guarantee

# **BATTERY SMILE-G3-BAT-4.5S**

• •



Model	SMILE-G3-BAT-4.5S
Physical Parameters	
Battery Type	LFP ( LiFePO4 )
Installation Method	Wall Mounted / Base Installation (Optional)
Dimension (W x D x H) ± 2	610 x 212.5 x 435 mm
Weight ± 1	53 kg
IP Protection	IP65
Warranty	10 Year Battery Performance Warranty
Electrical Parameters	
Rated Capacity	4.56 kWh
Depth of Discharge (DoD)	100%
Nominal Voltage	96 V
Operating Voltage Range	90 ~ 105.6 V
Operating Parameters	
Max. Charging Current	50 A
Max. Discharging Current	50 A
Operating Temperature Range	-20°C~50°C(Charge / Discharge)
Safety	Aerosol, explosion-proof valve
Relative Humidity	0 ~ 95% (No Condensation)
BMS	
Module Compatibility	G3-S3.6/S5/B5(1~4), G3-T4/5/6/8/10(1~6), G3-T12/15/20(2~6)
Rated Capacity (1~6 in series)	4.56 / 9.12 / 13.68 / 18.24 / 22.80 / 27.36 kWh
Monitoring Parameters	System voltage, current, cell voltage,
	cell temperature, PCBA temperature measurement
Communication	CAN
Certification	'
Transportation	UN38.3
Compliance	IEC 62619, IEC 62040, IEC 61000



- # +61 02 9000 7676
  techsupport@alphaess.au
  www.alphaess.com
  8/15-21 Gibbes Street, Chatswood,
  NSW 2067 Australia

- ⇔ +65 6513 1125 / +65 6513 1126
  ☎ Singapore@alpha-ess.com
  ⚠ 2 Corporation Road #01-06A Corporation Place 618494 Singapore

- a +39 339 462 4288

  info@alpha-ess.it

  www.alphaess.com

  Via Don Minzoni, 17,Calenzano
  Firenze 50041 Italy