

• YOUR
• SMART
• ENERGY



SMILE5

RESIDENTIAL SERIES

POWER

5 kW Inverter

CAPACITY

10.1 / 13.3 kWh

Battery Modular

Expandable to 80 kWh



reddot design award 2018



product
design award 2018



5kW single phase hybrid inverter

Fast response

UPS ability

24/7 Monitoring

- S**elf sufficient
- M**odular battery
- I**ntelligent control
- L**ong lifespan
- E**ssential load protected
- 5** kW system



SMILE5



Model		SMILE5
System Specification		
Rated Output Power	5000 W	
Rated Output Apparent Power	5000 VA	
Capacity Range	10.1 ~ 60.6 kWh(96% DoD)	13.3 ~ 80 kWh(100% DoD)
Usable Capacity Range	9.7 ~ 58.1 kWh	13.3 ~ 80 kWh
Battery Chemistry	LFP (LiFePO4)	
IP Protection	IP65	
Warranty	5 Year Product Warranty, 10 Year Battery Warranty	

Inverter Technical Specification			
Model	SMILE5-INV	Rated Output Apparent Power (Backup Port)	5000 VA
Coupling	Hybrid	Max. AC input Power (Grid Port)	7500 W
Max. PV Input Power	7500 W	Rated Output Current (Grid Port)	21.7 A
Max. PV Input Current	15 A / 15 A	Max. AC Output Current (Grid Port)	21.7 A
Max. PV Input Voltage	550 V	Rated Output Current (Backup Port)	21.7 A
Start-up input voltage	90 V	Max. AC Output Current (Backup Port)	21.7 A
Rated PV Input Voltage	360 V	Max Inverter Efficiency	96.50%
MPPT Number/Max. Input Strings Number Per MPPT	2/1	Backup	UPS
MPPT Voltage Range	70 ~ 540 V	Communication	Ethernet / WIFI
Max. PV Short-circuit Current	18 A / 18 A	Humidity	0 ~ 90% (No Condensing)
Max. Charging/Discharging Current	100 A	Dimension (W x D x H)	610 x 210 x 627 mm
Max. Charging/Discharging Power	5000 W	Weight	27.7 kg
Rated Frequency	50 / 60 Hz	Safety	IEC 62109
Rated Voltage	230 V	EMC	EN 61000-6-1 / EN 61000-6-3
Rated Output Apparent Power (Grid Port)	5000 VA	Grid Regulation	AS4777.2.2020

Battery Technical Specification		
Module Model	SMILE-BAT-10.1P	SMILE-BAT-13.3P
Module Capacity	10.1 kWh	13.3 kWh
Module Nominal Voltage	48 V	48 V
Operating Temperature Range	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*
Max. Modules in Parallel	6	6**
Max. Charging / Discharging Current	100 A	100 A
Cycle Life	8000***	8000***

* When the ambient temperature is too low or too high, the performance of battery may be limited.

** ≥2 needs to install expansion pack

*** Under specific test conditions



Alpha ESS Co., Ltd.

+86 513 8060 6891
info@alpha-ess.com
www.alphaess.com
Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Alpha ESS Suzhou Co., Ltd.

+86 512 6828 7609
info@alpha-ess.com
www.alphaess.com
Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou 215000

Alpha ESS Europe GmbH

+49 610 3459 1601
europe@alpha-ess.de
www.alphaess.de
Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

Alpha ESS Australia Pty. Ltd.

+61 402 500 520
info@alpha-ess.com
www.alphaess.com

Alpha ESS Italy S.r.l.

+39 339 462 4288
info@alpha-ess.it
www.alphaess.com
Via Don Minzoni, 17, Calenzano Firenze 50041

Alpha ESS UK Ltd.

+44 145 354 5222
info@alpha-ess.com
Drake House, Long Street, Dursley, gl11 4hh

Alpha ESS International Pte. Ltd.

+65 6513 1125 / +65 6513 1126
Singapore@alpha-ess.com
2 Corporation Road #01-06A Corporation Place Singapore 618494

Alpha ESS USA, Inc.

+1 408 368 7828
usa@alpha-ess.com
Unit 5, 2180 S Ivanhoe St, Denver, CO 80222

Alpha ESS Korea Co., Ltd.

info@alpha-ess.com
2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea